

## Cat.5e Surface Mount Wall Box 2 ports



### Materials Specifications

**Plastic Body** : Fireproof ABS UL-94V0

**RJ-45 Jack** : Housing-PBT/

UTP 8P8C 50 micro inches gold plated

**PCB** : FR-4 / 1.6mm UL-94V0

**IDC Body** : Fireproof ABS UL-94V0

**IDC Pin** : Bronze & Tinned

**Color Code** : T568 A/B

**IDC Description** : For 22-26 AWG / For 110 or LSA+ punch-down Tool

**Length** : 80mm **Depth** : 80mm **Height** : 28mm

### Electrical Specifications

**Insulation Resistance** : 500M ohms (min.)

**Contact Resistance** : 20m ohms (max.)

**Current Rating** : 1.5 Amps .

**DC Resistance** : 0.1 ohm (max.)

**Withstanding Voltage** : 1000 VAC RMS @ 60Hz / 1 min.

### Mechanical Specifications

**IDC Punch Down Cycle** : Over 25 Cycles (min.)

**RJ-45 Jack Insertion Cycle** : Over 2000 Cycles (min.)

**Operation Temperature** : -40 ~ +70 degree / C

### ITEM No

### Description

NOR-B2-C5e  
 30502002

Cat.5e Surface Mount Wall Box 2 ports