



- Gemäß TIA/EIA-568-C.2 Cat. 6A
- U/UTP 4x2xAWG24/7
- LSZH IEC332-1-ROHS konform
- RJ45 50µ" IEC60603-7-41
- Umspritzte Knickschutzülle
- Integrierter Klinsenschutz
- Für 10Gigabit Ethernet
- Eindeutige Seriennummer
- 100% Test inkl. Testprotokoll

- Follow TIA/EIA-568-C.2 Cat. 6A
- U/UTP 4x2xAWG24/7
- LSZH IEC332-1-ROHS compliant
- RJ45 50µ" IEC60603-7-41
- Moulded boot
- Integrated latch protection
- For 10Gigabit Ethernet
- Marked with serial number
- 100% test incl. protocol

Label printing:

Premium Patchkabel 500 LSZH
 CLASS EA U/UTP (length m, colour)
 Premium Patchcable 500 LSZH
 CLASS EA U/UTP (length m, colour)
 (ORDER NO)



WIRE CONNECTION TABLE								LENGTH	MOLD NO.
white/ orange	orange	white/ green	blue	white/ blue	green	white/ brown	brown		
A1	A2	A3	A4	A5	A6	A7	A8	(A+100)*[18(0)]*[18(0)]	02-088
B1	B2	B3	B4	B5	B6	B7	B8		

DWG NO.

K8103XX.X

TITLE

CAT.6A U/UTP PATCH CORD

UNIT	SCALE	SHEET
mm	1/1	1/1
DRAWN DATE	PROJ.	REV
10.05.2012		1
APPROVAL	CHECKED	DRAWN

Remark:

- ① Cable: Cat. 6A U/UTP, Stranded Bare Copper, 4Pairs Wires, 24AWG, Jacket LSZH, OD: 6.0mm;
- ② Plug: Cat. 6A Unshielded Type Plug with 3 Prongs, 50µ", 8P8C, UL94-V2, Mating Cycle >1200.
- ③ Packing: 1PC/OPP Bag with Label.
- ④ Cableprinting: Cat.6A PREMIUM Patchcord U/UTP 4x2xAWG24/7 ISO/IEC11801 TIA/EIA-568-C.2 ***10Gigabit Ethernet***

Testing: 100% Cat. 6A Channel Test with 4 Connectors.
 All materials are RoHS compliant.

